

# SOFT CHROME

2.300



Scaldasalviette in acciaio  
Steel towel rails

• La garanzia è di 2 anni

• 2 years warranty

## Dati tecnici Technical data

Modello Model	Altezza Height mm	Larghezza Width mm	Interasse Distance between centers mm	Resa termica Heat output EN442 $\Delta t = 50$ K Watt	Resa termica Heat output EN442 $\Delta t = 30$ K Watt
SOFT CHROME	800	450	400	<b>227</b>	123
SOFT CHROME	1200	450	400	<b>376</b>	203
SOFT CHROME	1400	450	400	<b>446</b>	241
SOFT CHROME	1800	450	400	<b>569</b>	307
SOFT CHROME	800	500	450	<b>253</b>	137
SOFT CHROME	1200	500	450	<b>397</b>	215
SOFT CHROME	1400	500	450	<b>490</b>	265
SOFT CHROME	1800	500	450	<b>621</b>	335
SOFT CHROME	800	550	500	<b>277</b>	150
SOFT CHROME	1200	550	500	<b>450</b>	243
SOFT CHROME	1400	550	500	<b>535</b>	289
SOFT CHROME	1800	550	500	<b>672</b>	363
SOFT CHROME	800	600	550	<b>302</b>	163
SOFT CHROME	1200	600	550	<b>475</b>	257
SOFT CHROME	1400	600	550	<b>560</b>	302
SOFT CHROME	1800	600	550	<b>697</b>	375

- Pressione massima d'esercizio è di 600 kPa (6 bar)
- I valori di resa termica sono conformi alla norma europea UNI EN 442-2
- The maximum operating pressure is 600 kPa (6 bar)
- Thermal output comply with the European standard UNI EN 442-2

